





Information Kiosk GK-Series









Self service - Any Time, Any Where

## Technical Specifications

	GK-319 (Thin Client Based)	GK-419 (Processor Based)
Construction	Enclosure : 1.6 mm thick CRCA steel sheet, polymer powder coated sheet designed to work in harsh environmental conditions. Floor mounted with permanent base and screw less chassis.	
	Disp	olay
Туре	Colour LED Touch Monitor with LED back light	
Size	48.3 cm (19 inches)	
Resolution	1280 x 1024 for 48.3 cm display	
Touch Screen type	SAW type with 6 mm antiglare & overlay tempered vandal resistant glass	
LED Touch Panel	250 CD/m2 (NITS) Brightness	
	System Details	
Processor	Intel DUAL CORE 1.8GHz or higher	Embedded Processor 2.13 GHZ or Higher
Chipset	Suitable chipset for processor	Suitable chipset for processor
Memory	1GB or Higher	2GB
ODD	Provision to connect external CD ROM	DVD (RW)
HDD/Storage	1 GB power Flash or higher	250GB or Higher
Expansion I/O	2PS -2/1USB,3 USB ,LAN 10/100,VGA	1PS -2/1USB,3 USB ,LAN 10/100,VGA
Audio	1 x Line-out / 1 x Line-in	
Speaker	2 x 1.5 watt, RMS Stereo speaker	
Operating System	Windows 7 embedded (Pre-loaded)	Windows 7 Professional (Pre-loaded)
Antivirus	NA	Norton Anti Virus / McAfee or equivalent with 1-year license
Environment		
Power Supply	180 – 240V, 50 Hz, AC Supply	
EMC & Safety	FCC Class B/CE Marking (only for CPU & display	
Power Consumption	80 watts	120 watts

Add On Items		
PR-85K	Thermal Printer	
KB-64	Metallic Keyboard with Track Ball (USB or PS/2)	

## Essae-Teraoka Pvt. Ltd.



410, 100ft Road, 4th Block, Koramangala, Bengaluru-560 034



info@essae.com



http://www.essae.com



+91 80 3021 3021 +91 80 3021 3001



1-800-425-3111







Form no. CAT-GK-Series-052-R02

▲ Factories in Bengaluru and Goa ▲ 47 Branch Offices ▲ 250+ Service engineers ▲ 350+ Resellers/Partners