

# INTEGRATED FANLESS POS

## Delta Series

Integrated & Compact solution without any messy cables  
using Industrial grade Fanless motherboard for high reliability





Integrated Rear Customer display option



Integrated 3-track MSR (option)



Durable Metal Housing with efficient thermal management

Description	Integrated Point of Sale (POS) system					
Model	Delta-AF	Delta-AFT	Delta-P	Delta-PT	Delta-C	Delta-CT
Processor	Intel ATOM® N270 1.6GHz		Intel Pentium Dual Core® E5300 2.6GHz or Higher		Intel Core2Duo® E7400 2.8GHz or Higher	
Thermal management	COMPLETELY FANLESS SYSTEM			3 x Cooling fans		
Chipset	Intel 945GSE			Intel 945GC		
Touch Screen	N.A	5-Wire Resistive (USB Interface)	N.A	5-Wire Resistive (USB Interface)	N.A	5-Wire Resistive (USB Interface)
USB	4			2		
LAN	2			1		
Mother Board	Industrial Grade Motherboard (Mini-ITX 17 cm x 17 cm)					
Standard Memory	1 GB					
Interface ports	3 x Serial, 1 x Parallel, 2 x PS/2, 1 x Audio					
Hard disk	80 GB or Higher					
Operating System Support	Windows Embedded for Point of Service (WePOS) Windows XP Professional & Vista Business					
Operator Display	15" TFT LCD Color					
Display Tilting Angle	15 ~ 80 Degrees					
Dimension (mm)	375 (W) x 335(D) x 350(H)					
Factory options	<ul style="list-style-type: none"> <li>• CD-810R Integrated customer display</li> <li>• Magnetic Stripe Reader (MSR)</li> </ul>					

