

POS-534

POS System

Essae[®]
...for Excellence



True FLAT
PCAP Touch



IP 54

Display



Signature
Design



A Compact yet powerful All-in-One POS System with Built-in Printer

Saves precious counter space & avoids messy cabling

Technical Specification

CPU	Intel Bay Trail CPU J1900 2.40 GHz
Chipset	CPU Intergrated
Operator Display	
Size	35.56 cm (14") TFT LCD
Maximum Resolution	1366 x 768 (16:9)
Touch Screen	True FLAT PCAP Touch
Tilt Adjustment	0° ~ 90° (w/o LCM)
Memory	
System Memory	4 GB DDR3
Storage Memory	64 GB SSD
External Interface Ports	
USB	4 x USB 3.0/2.0, 1 x USB 2.0 at Front
Serial Port(DB9)	3 x RJ48 (Powered RS 232) (Default 0 V; 0 V / 5 V / 12 V)
LAN	1 x RJ45 (Gigabit LAN)
Cash Drawer	1 x RJ11 (Default 19 V; 12 V / 19 V)
DC Jack	1 x 4 Pin w/lock
Audio	2 x 2 W (Option)
Control / Indicator	
Printer Feed Button	1
Printer LED Indicator	3 (Paper, Error, Power)
Power	
Power Adapter	120 W / 19 V
Peripheral	
Built-in Printer	Paper width 80 mm, 170 mm/sec, Auto cutter
MSR	3-Track MSR (Option)
Customer Display	LCM Display 20 x 2 Characters (Option)
Certificate	
EMC & Safety	FCC Class A, CE Mark, LVD
Environment	
Dust & Water Proof	IP54 Front Display
Operating Temperature	0° C ~ 35° C
Storage Temperature	-20° C ~ 60° C
Humidity	20 % ~ 85 % RH non-condensing
Dimension (W x D x H)	363 x 188 x 340 mm
Net Weight (without accessories)	5 kg
Operating System	Windows 10 IoT ENT 2016 LTSB
Supported	Windows POSReady 7 Linux (Subject to confirmation)

Accessories



Customer Display



MSR

Essae-Teraoka Pvt. Ltd.

410, 100ft Road, 4th Block,
Koramangala, Bengaluru-560 034

info@essae.com

http://www.essae.com

+91 80 2511 3021

1-800-425-3111

0-78488 12346

Essae[®]
...for Excellence

Your Essae representative

Note: Specifications are subject to change without notice. Other names and logos used are property of respective brands.