




# POS-615

POS System

**Essae**<sup>®</sup>  
...for Excellence




Powered by the latest generation Core i3/i5 Processor. Delivers exceptional Performance & Power even in the most demanding applications.



## Technical Specifications

Model	POS-615B	POS-615C	
CPU	Intel Baytrail J1900 QUAD CORE 2.00 Ghz Processor Embedded, Low Power, FANLESS Processor, 2 MB Cache Memory Intel	Intel Core i3 7100T 7 <sup>th</sup> gen 3.40 Ghz processor 3 MB Cache Memory	Intel Core i5 <sup>th</sup> -7500T 7 <sup>th</sup> gen 2.70 Ghz Processor 6 MB Cache Memory
Chipset	Baytrail J1900 with Integrated Graphic Chipset	Intel H1 10 Chipset	
<b>Operator Display</b>			
Size	38.1 cm (15") TFT LCD with LED Backlight, Anti-glare		
Maximum Resolution	1024 x 768		
Brightness	350 nits		
Touch Screen	Projected Capacitive Touch (PCAP) - True FLAT		
<b>Memory</b>			
Storage Memory	128 GB Solid State Disk (SSD) or 500 GB HDD		
System Memory	4 GB DDR3L RAM (expandable upto 8 GB)	4 GB DDR4 RAM (expandable upto 16 GB)	
<b>External Interface Ports</b>			
USB	6	5	
Serial (DB9)	2	4	
Network	1 x Gigabit LAN	2 x Gigabit LAN	
Display Port	1 x VGA	1 x HDMI	
Audio	1 x Line-in, 1 x Line-out		
Factory Options	Wi-Fi LAN Module (Mini-PCle)		
<b>Environmental</b>			
Operating Temperature	5°C ~ 40°C		
Storage Temperature	-20°C ~ 55°C		
Power Adapter	DC 12 V / 5 A, 60 W		
Dimension (W x D x H)	4° tilt angle : 382 mm x 220 mm x 356 mm 84° tilt angle : 382 mm x 294 mm x 300 mm		
<b>Optional Accessories</b>			
Printer	Thermal printer, 79.5±0.5 mm paper, 220 mm/sec, Auto-cutter 2D Barcode : QR code support, Interface : Serial+USB+LAN		
Cash Drawer	5-Bill/8-Coin Metal Cash Drawer with Lock & Key and micro-switch		
MSR	3 Track-OPOS Compliant, USB interface		
Customer display	20 chars x 2 lines Customer Display 9.7 inch Second Display Non Touch		
Mounting Options	VESA-compliant Wall Mount Kit		
Net Weight	6.1 kg (approx)		
<b>Operating System</b>			
Operating System Supported (Both 32-bit & 64-bit versions)	Windows 10 IoT Enterprise 2016 LTSB Entry Windows Embedded POS Ready 7 Linux (subject to confirmation)	Windows 10 IoT Enterprise 2016 LTSB Value Windows Embedded POS Ready 7 Linux (subject to confirmation)	

Accessories



MSR



20 chars x 2 lines  
Customer Display



9.7 inch Second display  
Non-Touch

## Essae-Teraoka Pvt. Ltd.

410, 100ft Road, 4th Block,  
Koramangala, Bengaluru-560 034

info@essae.com

http://www.essae.com

+91 80 2511 3021

1-800-425-3111

0-78488 12346



Your Essae representative

Note: Specifications are subject to change without notice. Other names and logos used are property of respective brands.