


# POS-615


POS System

**Essae**<sup>®</sup>  
...for Excellence




  
11th Gen  
CORE i3  
Processor

  
SSD  
128 GB

  
4GB  
RAM

  
3  
YEAR  
WARRANTY

  
True FLAT  
PCAP Touch

  
Windows 10  
IoT


Powered by the latest Core i3 11<sup>th</sup> Gen Processor. Delivers exceptional Performance & Power even in the most demanding applications.



## Technical Specifications

Model		POS-615C	
CPU	Intel Core i3 7100T 7 <sup>th</sup> gen 3.40 GHz Processor 3 MB Cache Memory	Intel Core i5 -7500T 7 <sup>th</sup> gen 2.70 GHz Processor 6 MB Cache Memory	Intel Core i3 1115G4 11 <sup>th</sup> gen 3.00 GHz up to 4.10 Ghz Processor 6 MB Cache Memory
<b>Operator Display</b>			
Size	38.1 cm (15") TFT LCD with LED Backlight, Anti-glare		
Maximum Resolution	1024 x 768		
Brightness	350 nits		
Touch Screen	Projected Capacitive Touch (PCAP) - True Flat		
<b>Memory</b>			
Storage Memory	128 GB Solid State Disk (SSD) or 500 GB HDD	128 GB M.2 NVMe SSD or 256 GB NVMe SSD	
System Memory	4 GB DDR4 RAM 2 x SO-DIMM Slot (Expandable up to 16 GB)	4 GB DDR4 RAM 1 x SO-DIMM Slot (Expandable up to 32 GB)	
<b>External Interface Ports</b>			
USB	5	6	
Serial (DB9)	4 x Serial	3 x COM	
Network	2 x Gigabit LAN	1 x Gigabit LAN	
Display Port	1 x HDMI	1 x HDMI	
Audio	1 x Line-in, 1 x Line-out	1 x Line-out & Mic in	
Factory Options	Inbuilt Wi-Fi		
<b>Environmental</b>			
Operating Temperature	5 °C ~ 40 °C		
Storage Temperature	-20 °C ~ 55 °C		
Power Adapter	DC 12 V / 5 A 60 W		
Dimension (W x D x H)	4° tilt angle : 382 mm x 220 mm x 356 mm 84° tilt angle : 382 mm x 294 mm x 300 mm		
<b>Optional Accessories</b>			
Printer	PR-65 and PR-75 Thermal printer, 79.5±0.5 mm and 82.5 ± 0.5mm paper, 220 mm/sec, Auto-cutter 2D Barcode : QR code support, Interface : Serial+USB+LAN		
Cash Drawer	5-Bill/8-Coin Metal Cash Drawer with Lock & Key and Micro Switch		
MSR	3 Track-OPOS Compliant, USB interface		
Customer display	20 chars x 2 lines Customer Display 9.7 inch Second Display Non Touch		
Mounting Options	VESA-compliant Wall Mount Kit		
Net Weight	6.1 kg (approx)		
<b>Operating System</b>			
Operating System Supports	Windows 10 IoT Windows Embedded POS Ready 7 Linux (subject to confirmation)	Windows 10 IoT Linux (subject to confirmation)	

### Accessories



MSR



20 chars x 2 lines  
Customer Display



9.7 inch Second display  
Non-Touch

## Essae-Teraoka Pvt. Ltd.

410, 100ft Road, 4th Block,  
Koramangala, Bengaluru-560 034

info@essae.com

http://www.essae.com

+91 80 2511 3021

1-800-425-3111

0-78488 12346



Your Essae representative

Note: Specifications are subject to change without notice. Other names and logos used are property of respective brands.