

POS-415N

POS System

Essae[®]
...for Excellence



12th Gen Processor



PCAP Touch



Windows



M.2 NVMe SSD



Wi-Fi



Powered by Intel 12th Gen N95
Superlative performance at competitive value!



Technical Specifications

Model	POS-415N
CPU	Intel Alder Lake N95, up to 3.40 GHz, 12th Gen Processor
Storage Memory	128 GB M.2 NVMe SSD or 256 GB M.2 NVMe SSD
System Memory	4 GB or 8 DDR4 RAM 1 x SO-DIMM Slot
Operator Display	
Size	38.1 cm (15") TFT LCD with LED Backlight
Resolution / Brightness	1024 x 768 / 350 nits
Touch Screen	Projected Capacitive Touch (PCAP) - True Flat
External Interface ports	
USB	5
Serial (DB9)	3
Network	1 x Gigabit LAN
Display Port	1 x HDMI (Independent)
Audio	1 x Line out & Mic in
Factory options	1 x M.2 Wi-Fi + BT
Environmental	
Operating Temperature	5°C ~ 40°C
Power Adapter	DC 12 V / 5 A
Dimension (W x D x H)	45° tilt angle : 382 mm x 256 mm x 355 mm
Optional Accessories	
Printer	Thermal printer, 79.5 + 0.5 mm paper, 220 mm/sec, Auto-cutter 2D Barcode : QR code support, Interface : Serial+USB+LAN
Cash Drawer	5-Bill/8-Coin metal cash drawer with lock & key and micro switch
MSR	3 Track-OPOS compliant, USB interface
Customer display	20 chars x 2 lines customer display 9.7 inch second display non touch
Mounting Options	VESA-compliant wall mount kit
Net Weight	5.3 kg (approx)
Operating System	
Operating System Supports	Windows 10 IoT, Linux (subject to confirmation)

External Interface ports



Optional accessories



Second display



MSR



2 lines customer display

Essae-Teraoka Pvt. Ltd.

#410, 100ft Road, 4th Block,
Koramangala, Bengaluru-560 034

info@essae.com

https://www.essae.com

+91 80 2511 3021

1-800-425-3111

+91 78488 12346



Your Essae representative

Form No. : 27854-CAT-POS-415N-101 R02